

## Energy and Time Saving Intelligent PoE Management Functions

### BSP-360

Industrial Renewable Power 5-Port Gigabit Managed Switch with 4-Port 802.3at PoE+

- Efficient MPPT charge function
- 5-port 10/100/1000BASE-T RJ45 copper with 4-port IEEE 802.3af/at PoE Injector function (Port 1 to Port 4)
- Solar voltage rating of 24-45V
- 2 x 24V DC output up to 24W
- Maximum PoE budget of 120W



### WGR-500-4PV

Industrial Wall-mount Gigabit Router with 4-Port 802.3at PoE+ and LCD Touch Screen

- 2.4-inch color LCD touch screen with management functions
- IPv6 WAN/LAN support
- Firewall with 802.1Q VLAN security
- Hardware NAT accelerates Internet NAT routing performance
- PoE schedule, scheduled power recycling, PD alive check



### WGS-4215-16P2S

Industrial 16-Port 10/100/1000T 802.3at PoE + 2-Port 100/1000X SFP Wall-mounted Managed Switch

- 16-Port IEEE 802.3af/at Power over Ethernet/end-span PSE
- 240-watt PoE budget/remote PoE power control
- IPv6/IPv4 Web-based/Telnet/SNMP v1/v2c/v3 remote management
- Compact IP30 metal case with fanless design
- Fixed wall mounting, magnetic wall mounting and DIN-rail installation



## Cost-effective Unmanaged Series

### FGSW-2022VHP

12-Port 10/100TX 802.3at PoE + 4-Port 10/100TX 802.3bt PoE + 2-Port Gigabit TP + 2-Port SFP Ethernet Switch with LCD Management

- IEEE 802.3at/bt PoE standard compliant
- 300-watt PoE budget; each 802.3bt port has about 60W output power capability
- 5 manual buttons for LCD management
- 2 10/100/1000BASE-T TP and 2 100/1000BASE-X mini-GBIC SFP interfaces
- Power low-voltage, power over-voltage and PSE over-temperature protection



### FGSW-1822VHP

16-Port 10/100TX 802.3at PoE + 2-Port Gigabit TP + 2-Port SFP Ethernet Switch with LCD PoE Monitor

- 300-watt PoE budget
- 5 manual buttons for LCD Management
- 2 10/100/1000BASE-T TP and 2 1000BASE-X mini-GBIC SFP interfaces
- VLAN Mode to isolate ports to prevent broadcast storm and defend DHCP spoofing
- Power low-voltage, power over-voltage and PSE over-temperature protection



### NVR-2516P

H.265 25-ch 4K Network Video Recorder with 16-Port PoE

- H.265/H.264 and dual streaming compression technology
- Up to 4K resolution recording and playback for clear monitoring
- 16 independent PoE+ network interfaces
- PVMS and smart event for detailed monitoring
- Remote live viewing through Smart App for 24/7 viewing
- 1 eSATA, 4 SATA HDD drawer (3.5") and 4K HD/VGA output



### GSD-1222VHP

8-Port 10/100/1000T 802.3at PoE + 2-Port 10/100/1000T + 2-Port 1000X SFP Ethernet Switch with PoE LCD Monitor

- 8-port IEEE 802.3af/at Power over Ethernet end-span PSE
- 2-inch color LCD with smart management functions
- Supports "Standard", "VLAN" and "Extend" operation modes
- The "Extend" mode features 30-watt PoE transmit distance of 250m at speed of 10Mbps and VLAN isolation
- 6KV DC Ethernet ESD protection and 4KV DC surge immunity



### GSD-1008HP

8-Port 10/100/1000T 802.3at PoE + 2-Port 10/100/1000T Desktop Switch (120 watts)

- 10-port 10/100/1000BASE-T Gigabit Ethernet RJ45 copper
- Complies with IEEE 802.3at Power+ over Ethernet end-span PSE
- 120-watt PoE budget
- Supports "Standard", "VLAN" and "Extend" operation modes
- The "Extend" mode features 30-watt PoE transmit distance of 250m at speed of 10Mbps and VLAN isolation
- Noiseless design and Plug & Play



### GSD-2022P

16-Port 10/100/1000T 802.3at PoE + 2-Port 10/100/1000T + 2-Port 1000X SFP Desktop Switch

- Supports up to 32W per PoE+ port w/ 185W PoE budget
- Hardware-based DIP switch for Standard, VLAN or Extend mode selection
- VLAN mode is to isolate ports to prevent broadcast storm and defend DHCP spoofing
- Extend mode enables 8 PoE ports to support a max. distance extension of 250m
- Two 1000BASE-SX/LX/BX SFP slots for long distance data uplink



DISTRIBUIDOR OFICIAL



## PoE for Surveillance Solution

PLANET PoE solution features 802.3bt PoE++, Intelligent PoE functions, managed/unmanaged series, ONVIF and the extension technology to satisfy a variety of commercial and industrial surveillance deployment demands.

### Management Series: L3, L2/L4 PoE Switches

#### GS-6320-24UP2T2XV

L3 24-Port 10/100/1000T 802.3bt PoE + 2-Port 10GBASE-T + 2-Port 10G SFP+ Managed Switch with LCD Touch Screen and Redundant Power

- 2.4-inch color LCD touch screen with management functions
- Layer 3 OSPFv2 dynamic routing, IPv4/IPv6 static IP routes
- 2 10GBASE-T/N-BASE-T RJ45 ports
- 36-60V DC and 100-240V AC redundant power for system
- ITU-T G.8032 ERPS (Ethernet Ring Protection Switching)



#### GS-5220-16UP2XVR

L3 16-Port 10/100/1000T 802.3bt PoE + 2-Port 10G SFP+ Managed Switch with LCD Touch Screen

- 2.4-inch color LCD touch screen with management functions
- Supports up to 75 watts of PoE power for each PoE port
- PoE schedule, scheduled power recycling, PD alive check
- 2 10GBASE-SR/LR SFP+ slots, compatible with 1000BASE-SX/LX/BX SFP
- 36-60V DC and 100-240V AC redundant power system



#### GS-5220-8UP2T2X

Layer 3 8-Port 10/100/1000T 802.3bt PoE + 2-Port 10/100/1000T + 2-Port 10G SFP+ Managed Switch

- 8-port Gigabit 802.3bt PoE++ end-span/mid-span PSE w/ 75W output
- 2-port 1/10G BASE-X SFP+ for Gigabit uplink
- Layer 3 OSPFv2 dynamic routing, 128 static IP routes and route summarization
- ITU-T G.8032 ERPS (Ethernet Ring Protection Switching)
- Convenient and Smart ONVIF devices with detection feature



#### GS-4210-24PL4C

24-Port 10/100/1000T 802.3at PoE + 4-Port Gigabit TP/SFP Combo Managed Switch (440W PoE budget)

- 440-watt PoE budget / Intelligent PoE management
- IEEE 802.1Q VLAN, GVRP, Voice VLAN and Private VLAN
- IEEE 802.1s MSTP, IPv4 IGMP snooping and IPv6 MLD snooping
- 802.1x RADIUS and TACACS+ authentication / L2-L4 ACL
- IPv6 web interface; SNMP v1, v2c and v3; SSH; SSL management



#### WGSW-20160HP

L2+ 16-Port 10/100/1000BASE-T 802.3at PoE + 4-Port Gigabit TP/SFP Combo Managed Switch

- IPv4/IPv6 dual-stack management, supporting SSH, TLS and SSL management
- DHCP Snooping, Dynamic ARP Inspection and IP Source Guard
- 802.1x Port-based and MAC-based network access
- RADIUS and TACACS+ authentication
- IPv4 and IPv6, L2 to L4 Access Control List



11F., No 96, Minquan Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)  
Tel: +886-2-2219-9518 Fax: +886-2-2219-9528 E-mail: sales@planet.com.tw

PLANET reserves the right to change specifications without prior notice. All brand names and trademarks are property of their respective owners. © PLANET Technology Corporation DM-POES0121



Avda. Fuente Nueva, 12. 28703 San Sebastián de los Reyes - Madrid - España  
Tel.: +34 916588760. Fax: +34 916588769  
E-mail: marketing@cartronic.es  
www.grupocartronic.com  
www.linkedin.com/company/cartronic-group



## High PoE Budget for High Power Equipment

### IGS-5225-4UP1T2S

Industrial L2+ 4-Port 10/100/1000T 802.3bt PoE + 1-Port 10/100/1000T + 2-Port 100/1000X SFP Managed Switch

- IPv4/IPv6 dual-stack management, supporting SSH, TLS and SSL secure management
- DHCP Snooping, Dynamic ARP Inspection and IP Source Guard
- Remote Access Management Control
- PoE schedule, scheduled power recycling, PD alive check
- ERPS Ring Data Recovery time <10ms



### GS-4210-16UP4C

16-Port 10/100/1000T 802.3bt PoE++ plus 4-Port Gigabit TP/SFP Combo Managed Switch

- 400-watt ultra PoE budget and intelligent PoE management
- IEEE 802.1Q VLAN, GVRP, Voice VLAN and Private VLAN
- IEEE 802.1s MSTP, IPv4 IGMP snooping and IPv6 MLD snooping
- 802.1x RADIUS and TACACS+ authentication/L2-L4 ACL
- IPv6 web interface; SNMP v1, v2c and v3; SSH/SSL management



### IGS-6325-8UP2S2X

Industrial L3 8-Port 10/100/1000T 802.3bt PoE + 2-Port 1G/2.5G SFP + 2-Port 10G SFP+ Managed Ethernet Switch

- 8-port 10/100/1000BASE-T with 802.3bt PoE++
- 360-watt PoE budget/remote PoE power control
- -40 ~ 75 degrees C wide operating temperature
- 48 ~ 56V DC redundant power design
- IEEE 802.1w/1s STP, IEEE 802.1Q VLAN and IGMP snooping v2 and v3



### GS-6322-24P4X

L3 24-Port 10/100/1000T 802.3bt PoE + 2-Port 10GBASE-T + 2-Port 10G SFP+ Managed Switch with Dual Modular Power Supply Slots

- Power management supports RPS (1+1) or EPS (2+0) mode
- Supports PoE power up to 95 watts per port
- ERPS ring data recovery time < 10ms
- IP Routing Protocol: static and OSPFv2
- PoE schedule, scheduled power recycling, PD alive check
- IEEE 802.1Q VLAN, Q-in-Q Protocol-based and MAC-based VLANs



### IPOE-E174

Industrial 1-Port Ultra PoE to 4-Port 802.3af/at Gigabit PoE Extender

- 1-port ultra Power over Ethernet PD
- Supports PoE input power up to 60 watts
- 4-port IEEE 802.3af/at Power over Ethernet / end-span PSE
- Supports PoE output power up to 30 watts for each PoE port
- Extends the range of PoE for an additional 100 meters (328ft.)



### IGS-6325-8UP2S

Industrial L3 8-Port 10/100/1000T 802.3bt PoE + 2-Port 1G/2.5G SFP Managed Ethernet Switch

- 8-port 10/100/1000BASE-T with 802.3bt PoE++
- 360-watt PoE budget/remote PoE power control
- -40 ~ 75 degrees C wide operating temperature
- 48 ~ 56V DC redundant power design
- IEEE 802.1w/1s STP, IEEE 802.1Q VLAN and IGMP snooping v2 and v3



## Industrial Grade for Harsh Environment

### IGS-6325-16P4S

L3 Industrial 16-Port 10/100/1000T 802.3at PoE + 4-Port 1G/2.5G SFP Managed Ethernet Switch

- Layer 3 OSPFv2 dynamic routing, 128 static IP routes and route summarization
- ITU-T G.8032 ERPS (Ethernet Ring Protection Switching)
- PoE schedule, scheduled power recycling, PD alive check
- Convenient and Smart ONVIF devices with detection feature
- Supports Modbus/TCP protocol for device management and monitoring



### IGS-4215-8P2T2S

Industrial 8-Port 10/100/1000T 802.3at PoE + 2-Port 10/100/1000T + 2-Port 100/1000X SFP Managed Switch

- 8-port IEEE 802.3at/af Power over Ethernet (end-span PSE, 240W PoE budget)
- PoE schedule, scheduled power recycling, PD alive check
- LED indicators for PoE usage status (60W/120W/180W/240W)
- IEEE 802.1w/1s STP, IEEE 802.1Q VLAN, and IGMP snooping v2 and v3
- 48 ~ 56V DC redundant power design



### WGS-4215-8P2S

Industrial 8-Port 10/100/1000T 802.3at PoE + 2-Port 100/1000X SFP Wall-mount Managed Switch (-40~75 degrees C)

- 8-Port IEEE 802.3af/at Power over Ethernet/end-span PSE
- 200-watt PoE budget/remote PoE power control
- IPv6/IPv4 Web-based/Telnet/SNMP v1/v2c/v3 Remote Management

### IGS-5225-8P2T2S

L2+ Industrial 8-Port 10/100/1000T 802.3at PoE + 2-Port 10/100/1000T+ 2-Port 100/1000X SFP Managed Ethernet Switch

- 48-56V DC redundant power design
- IP30 aluminum case; DIN-rail and wall-mount design
- Supports PoE Power up to 36 watts for each PoE port
- PoE schedule, scheduled power recycling, PD alive check
- ERPS Ring Data Recovery time < 20ms



### IGS-5227-4MP2MT

Industrial IP67-rated 4-Port 10/100/1000T 802.3at PoE + 2-Port 10/100/1000T Managed Ethernet Switch

- 24-48V DC redundant power with 5-pin M23 A-coded interface
- IP67 aluminum case; DIN rail and wall-mount designs
- 144-watt PoE budget, remote PoE power control
- ERPS Ring Data Recovery time < 50ms
- IPv4/IPv6 Layer 3 static routing and route summarization



- Compact IP30 metal case with fanless design
- Fixed wall mounting, magnetic wall mounting and DIN-rail installation



## ONVIF supported

### GS-5220-16UP2XVR

L3 16-Port 10/100/1000T 802.3bt PoE + 2-Port 10G SFP+ Managed Switch with LCD Touch Screen

- 2.4-inch color LCD touch screen with management functions
- Supports up to 75 watts of PoE power for each PoE port
- PoE schedule, scheduled power recycling, PD alive check
- 2 10GBASE-SR/LR SFP+ slots, compatible with 1000BASE-SX/LX/BX SFP
- Supports ONVIF detection



### GS-5220-24UPL4XVR

L2+ 24-Port 10/100/1000T Ultra PoE + 4-Port 10G SFP+ Managed Switch with LCD Touch Screen

- 2.4-inch color LCD touch screen with management functions
- Supports up to 75 watts of PoE power for each PoE port
- PoE schedule, scheduled power recycling, PD alive check
- 4 10GBASE-SR/LR SFP+ slots, compatible with 1000BASE-SX/LX/BX SFP
- Redundant 100-240V AC/36-60V DC dual power



### IGS-10020HPT

L2+ Industrial 8-Port 10/100/1000T 802.3at PoE + 2-Port 1G/2.5G SFP Managed Switch with Wide Operating Temperature

- DC 12V-48V power input provides up to 36W PoE power per PoE port
- PoE schedule, scheduled power recycling, PD alive check
- ERPS Ring Data Recovery time < 10ms
- Cybersecurity can be enhanced with SNMPv3, SSH and SSL features
- Supports Modbus/TCP protocol for device management and monitoring



### WGS-5225-8P2SV

Industrial L2+ 8-Port 10/100/1000T 802.3at PoE + 2-Port 1G/2.5G SFP Wall-mount Managed Switch with LCD Touch Screen

- 2.4-inch color LCD touch screen with management functions
- ERPS Ring Data Recovery time < 20ms
- IPv4/IPv6 Layer 3 static routing
- Supports Modbus TCP/IP Protocol
- 802.3at PoE+ with intelligent PoE management



## Long Reach PoE Solution for Transmission Distance Extension

### LRP-422CST

Industrial 4-Port Coax + 2-Port 10/100/1000T + 2-Port 100/1000X SFP Long Reach PoE over Coaxial Managed Switch

- 4-port BNC Long Reach PoE with Data and Power transmitted over up to 1000m coax cable
- 48 ~ 56V DC redundant power design
- IP30 aluminum case; DIN-rail and wall-mount design
- PD Alive Check, Scheduled Power Recycling, Time-based PoE Schedule
- IPv6 Web interface/SNMP v1, v2c and v3/SSH/SSL management



### LRP-1622CS

16-Port Coax + 2-Port 10/100/1000T + 2-Port 100/1000X SFP Long Reach PoE over Coaxial Managed Switch

- 16-port BNC Long Reach PoE with Data and Power transmitted over up to 1000m coax cable
- 440-watt PoE budget centrally and remotely controlled
- Up to 25-watt power output to remote 802.3af/at complied PD
- PD Alive Check/Scheduled Power Recycling/Time-based PoE Schedule
- IGMP Snooping v2 and v3/MLD Snooping



### LRP-822CS

8-Port Long Reach PoE + 2-Port 10/100/1000T + 2-Port 100/1000X SFP Managed Switch

- 8-port BNC Long Reach PoE with Data and Power transmitted over up to 1000m coax cable
- 240-watt PoE budget centrally and remotely controlled
- Up to 25-watt power output to remote 802.3af/at complied PD
- PD Alive Check / Scheduled Power Recycling / Time-based PoE Schedule
- IGMP Snooping v2 and v3 / MLD Snooping



### LRP-101CE

1-Port Long Reach PoE over Coaxial Extender

- 1-port BNC with passive PoE PD
- 1-port 10/100T RJ45 with 802.3at PoE+ PSE to remote PoE IP camera/AP
- Supports PoE power up to 25 watts (depending on Power Source and Coaxial Distance)
- Power and Ethernet data transmission over coaxial up to 1km
- -20 ~ 70 degrees C operating temperature

