

# **ARENA 4806**

## Video and Data Wall Controller

TECHNICAL SPECIFICATIONS

#### Outputs

- Up to 24 FHD outputs
- Up to 6 UHD outputs
- HDMI/DVI interfaces

#### Inputs

- Analog Composite PAL/NTSC
- Analog VGA/Component
- Digital DVI/HDMI/3G-SDI
- 1080p60 or 1920x1200p60
- 4K support
- Video over IP (GbE)
- Stored content playback
- Remote Desktop over IP

#### Video Processino

- HD/SD encode/decode (HW)
- Video (MPEG-2/4, H264/5)
- Up/Down Scaling
- Post Processing
- High Resolution 2D/3D Images

#### **SERVICES AVAILABLE**

Planning & Consultation
Technical Support Installation
and Setup Maintenance
Application Support Extended
Warranty

NOTE: The Specification may change without notice. The actual products sold are different from areas. Please check the detailed Specification with your local dealers

www.nvusystems.com

The Arena 4806 is a video and data wall controller for 24x7 operations that offers a great cost-effective solution for up to 24 screens, multi-window display of any visual information.

This embedded platform fits into mission critical environment that requires media processing and monitoring of multiple diverse sources, connected via various networks.



Arena architecture combines the benefits of high quality, uncompressed video capture with the flexibility and convenience of network-based video distribution and sharing.

The controller provides high I/O port density for reduced space and power consumption.

# Features and Benefits

- Embedded system in 4U chassis
- Based on Windows 10 Pro, 64bit OS
- . High performance up to PCI-Express Gen 4.0 bus
- Multiple and flexible display configurations
- High density Up to 8 inputs capture cards
- Video and Remote-Display over IP network
- Intuitive setup and control
- Open XML API for platform monitoring and control
- Remote user options
- Security attributes
- HDCP support



## Main Chassis

- Rack mountable 19", 4U
- 3<sup>rd</sup> Gen Xeon scalable processor
- 240GB SSD ( RAID storage optional )
- 7 x PCIe slots
- 2 x RJ45 GbE LAN ports
- 2 x USB2.0 + 2 x USB3.2
- Dimensions: 465.2 x 430.0 x 176.0 (mm) 18.32" x 16.93" x 6.93"
- Packed: 590 x 560 x 300 (mm); 18 Kg
- Any control over Ethernet

### ARENA OPERATION MANAGEMENT- WALLBRIX

Arena Operation Management is a software application that provides complete configuration and control of the visual information being received, processed and displayed on the wall. It enables source selection and rendering into any displayed window, display layout selection and configuration. It is designed to fully exploit the uniquely powerful and flexible Arena architecture.

It can be accessed locally via VGA connected display or remotely through the network from any connected PC. In addition WallBrix SDK and XML APIs, enable easy integration with 3<sup>rd</sup> party control systems.



Avda. Fuente Nueva, 12. 28703 San Sebastián de los Reyes - Madrid - España

Tel.: +34 916588760. Fax: +34 916588769

E-mail: marketing@cartronic.es www.grupocartronic.com

www.linkedin.com/company/cartronic-group



